

Product information

DM Global Outlet R&MhealthLine, 80x86, 2x1-port

R824377
10 pcs



090.7632

Suitable for surface-mounted installations on walls and in ducts. Housing plus wallplate measures 80x86x67.5 mm. Cable entry at the side or the back. For use with cover frames and duct covers of Ø 60 mm in diameter or 56x56 mm cutouts.

Plastic: PC + ABS, Antibacterial

Suitable for RJ45 connection modules, connection module ISDN 2xRJ45 and fiberoptic connectors with support plates.

- Cover frame 80x86 mm
- 2-part faceplate 60x60 mm
- M3x12 screws
- Blind cover (when used as a 1-port outlet)
- Mounting plate, steel
- Label strips, blank

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Protection class IP	IP 20
Assembly	empty
Capacity (ports)	2 x 1
Outlet type	outlet

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Dimensions	80mm x 86mm (W x H)
Color Code RAL	9010 Pure white
Material	plastic: PC + ABS / Antibacterial

This outlet features an angled outlet hood of 30°, for surface-mounted installations, including a mounting plate, cover frame 80 x 86 mm, also including a labeling window and a module holder for 2 individual RJ45 modules, plus a blind cover for the use as a one-RJ45 outlet, to cover the unused port. Color: white (RAL 9010). Halogen-free in acc. with DIN/VDE 0472/815, and Antibacterial.