Product information

R&MhealthLine Patch Cord Cat. 6, U/UTP, 4P, LSZH, white, RJ45/u-RJ45/u, 3m

R825750 10 pcs



The shielded Cat. 6 R&MhealthLine Patch Cord reduces the risk of spreading bacterias and gorms as a result of tauching the patch cord

bacterias and germs as a result of touching the patch cord.

Cable identification: U/UTP Outer jacket: LSZH

Conductor diameter copper strand: AWG 26/7

Screened in pairs: No Overall screen: No

Outer diameter: max. 5.5 mm

Antibacterial: Yes

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE	
Standard	Compliant with Cat. 6 Class E (250 MHz) requirements: ISO/IEC 11801 ed. 2.2 Compliant with Cat. 6 component standard IEC 60603-7-4 Compliant with Cat. 6 component standard IEC 60603-7-5 Fulfilled the standard IEC 61935-2:2010 Antibacterial according to ISO 22196	
Protection class IP	IP 20	
PoE	Yes	
Connector class	connector	
Shielding connector (A)	unshielded	
Connector type (A)	RJ45	
Category connector (A)	Cat. 6	
Shielding connector (B)	unshielded	
Connector type (B)	RJ45	
Category connector (B)	Cat. 6	
Cable type	patch cord	
Category	Cat. 6	
Shielding	U/UTP	
Jacket material	LSZH, antibacterial equipped	
Cable overall diameter	5.5 mm	
Conductor	AWG 26/7	
Number of wires	8	
Stranding	4 pairs	
Wire type	stranded wire	

Mechanical Data



DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	3 m
Color Code RAL	9010 Pure white

Antibacterial cable, flexible, U/UTP, $4 \times 2 \times AWG$ 26/7, LSZH, color white (RAL 9010). Low-smoke in acc. with IEC 61034 and halogen-free in acc. with IEC 60754-1. Halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Mounted on both sides with antibacterial RJ45 connector compliant with Cat. 6 component standard. Key standard: IEC 60603-7 RJ45 category 6; IEC 60603-7-1 to 5. Strain-relief function in acc. with TIA 568-C. Complies with requirements of Cat. 6 for the establishing of transmission links of class E in acc. with ISO/IEC 11801 ed. 2.2, June 2011 and EN 50173-1, May 2011 (DIN EN 50173-1). Antibacterial characteristics according to ISO 22196.

	Description	PU	Product No.
Rass hooft line	WM Global Outlet R&MhealthLine, 80x80, 2x1-port	10 pcs	R824376
RASS HoodFilling	DM Global Outlet R&MhealthLine, 80x86, 2x1-port	10 pcs	R824377
	Hinged Dust Cover R&MhealthLine, white	10 pcs	R825747