


Product information

Central Loose Tube Cable A-D(ZN)W2Y, OM3, Eca, 6-fibers

R312794
2000 m



The outdoor cable for applications in harsh conditions. It contains a central gel-filled loose tube of a diameter of 2.8 mm for 2 - 16 fibers or 3.5 mm for 18 - 24 fibers. The outer sheath is made of a 0.155 mm corrugated steel armor plus a 1.5 mm PE sheath.

- Sheath: PE, black
- Fiber: multimode (MM) G50/125

030.1422 / similar product

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	IEC 60794-1-2 E1 IEC 60794-1-2 E11 IEC 60794-1-2 E3 IEC 60794-1-2 F1 IEC 60794-1-2 E4 IEC 60794-1-2 E7 IEC 60794-1-2 E10
Cable type	loose tube
Jacket material	PE
Fire rating	Fca
Cable jacket characteristics	Cable, water-tight
Cable protection	Steel-armored
Cable overall diameter	8.5 mm
Cable design	A-D(ZN)W2Y
Fiber type	multimode (MM)
Fiber class	OM3
Number of fibers	6
Conductor type	loose tube, gel-filled
Fiber diameter	G50 / 125 µm

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	2000 m
Color	black